

# MOLDTON 1010

Mineral oil based formwork release agent

## DESCRIPTION

MOLDTON 1010, is mineral oil based, mould release agent that provides easy separation of the moulds from concrete and creates smooth concrete surfaces.

## FIELD OF APPLICATION

- Steel, plastic, ply-wood formworks
- In applications requiring more efficient formworks

## ADVANTAGES

- Provides smooth and clean concrete surface.
- Easy and clean striking of formwork.
- Extends the life of the formwork.
- Allows a uniform, stain-free, smooth surface.
- Reduced formwork costs and workmanship.

## USE

- MOLDTON 1010 before application of mould release agent, the moulds should be dry and clean, concrete and rust residues must be removed.
- MOLDTON 1010, should be shaken well before the application.
- The application can be carried out one homogenous coat with brush, roller or spray.

## STORAGE CONDITIONS AND PACKAGING

The product must be stored above 5 °C. In case the product freezes it should be carefully mixed mechanically after thawing for restitution.

It is for sale as 25 kg plastic drum, 200 kg drums, 1000 kg plastic cubitainers.

## CONSUMPTION (m<sup>2</sup>)

Steel molds : 80 -120 ml

Ply-wood molds : 100 – 150 ml

Plastic molds : 120 – 200 ml

## SAFETY INFORMATION

The additive must be kept away from the skin and eyes. In case of any contact, it must be washed with water. When contacted with eyes one must immediately rinse it with water and medical support must be taken. Protective goggles / gloves / mask should be used during the usage of the admixture.

The Material Safety Data Sheet (MSDS) should be read for detailed information.